

AAHHi

www.AAHHi.com
Professional Two-Way Radio Manufacturer



D71 4W UV DMR & ANALOG PORTABLE RADIO



Clear Voice, Multiple Functions



ANALOG
DMR

Duan Band/Display/Standby/PTT

Radios with Dual Band capability can transmit and receive on both UHF and VHF radio bands, also dual display, dual watch and dual PTT.

Hands-free VOX

This hands-free feature allows you to get on with other manual tasks while you stay in touch with other users.

Digital Encryption

Some radios have encryption built in so that other radio operators cannot listen in to your communications.

Repeater Capable

These radios are capable of being used with a repeater station, which can greatly increase your communications range and reliability.

AES 256 Encryption

AES-256 encryption uses the 256-bit key length to encrypt as well as decrypt a block of messages.

Scrambler

A technology is used to scramble communications to prevent other radio users in the vicinity from listening to your conversations.

Noise Reduction (Optional Paid Feature)

Noise reduction is the process of removing noise from a signal, in order to improve background sound quality to be clearer.

Recorder (Optional Paid Feature)

The user enables to record and store short incoming audio, or record their own short message.

SPECIFICATION

General	
Frequency Range	136-174 & 400-470
Channel Capacity	3000
Zone Capacity	250
Channel Spacing	12.5/25kHz
Frequency Stability	±500Hz
Antenna Impedance	50Ω
Operating Voltage	DC 7.4V
Battery Capacity	1800mAh
Battery Life(5-5-90 Duty Cycle, High TX Power)	Analog: 12 hours Digital: 19 hours
Dimensions (ex ant, H×W×D)	132(H)×56(W)×35(D)mm
Weight	About 260g

Transmitter		Receiver	
Output Power	4W/1W	Sensitivity(Analog)	-123dBm@12dB SINAD
Analog FM Modulation	12.5 kHz: 11K0F3E 25 kHz: 16K0F3E	Selectivity(Digital)	≤-117dBm(Eers5%)
Digital 4FSK Modulation	12.5 kHz data: 7K60FXD 12.5 kHz data & voice: 7K60FXW	Adjacent Channel Selectivity	≥60dB
Conducted/Radiated Emission	< -36dBm [< 1 GHz]; < -30dBm [> 1 GHz]	Inter Modulation Response Rejection	≥60dB
Modulation Limiting	±2.5kHz @ 12.5 kHz ±5kHz @ 25kHz	CSQ Hum & Noise	< -45 dB@25K; < -40 dB@12.5K
FM Hum & Noise	< -45 dB@25K; < -40 dB@12.5K	Rated Audio Power Output	≤1000mW
Adjacent Channel Power	≤-65 dB@25K ≤-60 dB@12.5K	Rated Audio Distortion	≤3%
Audio Response	+1dB ~ -3dB	Conducted Spurious Emission	< -57 dBm [< 1 GHz]; < -47 dBm [> 1 GHz]
Modulation Distortion	≤5%	Co-channel Rejection	≥-12dB
Digital Vocoder Type	AMBE+2	Block	≥84dB
Digital Protocol	ETSI-TS102361-1,-2,-3	Received Signal To Noise Ratio	< -45 dB@25K; < -40 dB@12.5K
Carrier Frequency Tolerance	±500Hz		

All specifications are subject to change without notice due to continuous development.

ACCESSORIES

STANDARD ACCESSORIES



TP008



BL004
(1800mAh)



CC001
(for BL009, BL010)



PC2003



PP1002

OPTIONAL ACCESSORIES



BL003
(1800mAh w/Type-C)



BL005
(2200mAh)



BR006
(3000mAh)



CC002
(for BL008, BL011)



LP005



EE003



AAHHi

Quanzhou AAHHi Electronics Co., Ltd.

Address: No. 886 Jiangan Hi-Tech Industrial Park,
Licheng, Quanzhou, Fujian, China

Tel / What's App: +86-138-59707018 Post: 362005

Email: info@aaHHi.com Https://www.aaHHi.com



Facebook



Instagram



Threads



Name Card

AAHHi retains right to change the product design and specification. Should any printing mistake occur, AAHHi doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

AAHHi SSHHi NOONSO AAHHiWDM are registered trademarks of AAHHi.